



Pipe clamp ERS w/ Lining

Group: 1206

Application

Two-piece pipe clamp with double thread connection (M8/M10) and sound absorption lining for the installation of pipelines. Applicable for sound-absorbed installations according to DIN 4109 specifications.

Technical Data

Size [mm]	Working load (tension)	Tightening torque [Nm]
11 - 35	0,55 kN	1
39 - 66	0,80 kN	2
75 - 161	0,90 kN	2

Material: Steel, electro-galvanised
 Sound absorbing lining: EPDM, black

Size range [mm]	Material w x th [mm]	Thread connection	W [kg]	Qty. [Stück]	Part number
11 - 15	20 x 1,0	M8/M10	0,04	200	116766
15 - 19	20 x 1,0	M8/M10	0,04	180	116767
20 - 24	20 x 1,0	M8/M10	0,04	170	116768
25 - 28	20 x 1,0	M8/M10	0,04	130	116769
32 - 35	20 x 1,0	M8/M10	0,06	120	116771
39 - 46	20 x 1,2	M8/M10	0,06	90	116772
48 - 53	20 x 1,2	M8/M10	0,08	70	116773
54 - 58	20 x 1,2	M8/M10	0,08	50	116774
59 - 66	20 x 1,2	M8/M10	0,08	50	116775
75 - 80	20 x 1,5	M8/M10	0,10	60	116776
87 - 92	20 x 1,5	M8/M10	0,12	50	116777
107 - 115	20 x 1,5	M8/M10	0,14	50	116778
120 - 128	20 x 2,0	M8/M10	0,203	40	K117506
149 - 161	20 x 2,0	M8/M10	0,243	25	K117507